We serve the solution

temp-rite

Temp-Active



Insulated Pellet System with integrated heating core and induction heating device – for extended meal serving times

www.temp-rite.eu



We serve the solution

temp-rite – Your reliable partner for innovative and sustainable solutions in meal distribution.



temp-rite is double ISO-certified!

Quality management:

Hospitals, old people's homes and other care-providing institutions attach great importance to the quality of the services and products their suppliers deliver. temp-rite's Quality Management System meets all the requirements set out in DIN EN ISO 9001.

Ecological awareness:

temp-rite Germany also has DIN EN ISO 14001 environmental certification. This underlines just how seriously we take protecting the environment, and achieving a sustainable balancebetween commercial and ecological considerations.





temp-rite



2.

Temp-Active Advantage

Temp-Active Advantage is a classic meal distribution system consisting of:

- Bases with an active heating core
- an induction heating device
- insulated domes

The pellet system significantly extends the holding time for meals.

The functioning

The compact induction device made of stainless steel with a glass-ceramic plate and integrated guide enables efficient heating of the core through proven induction technology. During the holding time, the core evenly distributes heat to the plate, ensuring the food remains consistently warm at an optimal temperature.

1. Placement of the base into the integrated guide



Placing the plate with food onto the heated base

3.

Covering with an insulated dome Transport using a tray transport trolley to the patient or resident

5.

Comfortable

- Prevention of user errors through start-stop automation
- Visual and audible signals via colored LED status bar
- Easy cleaning of dishwasher-safe system components
- Space-saving and compact system

Reliable

4.

- Consistent serving temperature of the meals
- Long holding times (Guaranteed 60 min ≥ 60°C)*
- Even and constant heat transfer to the food
- Highly effective insulation for temperature maintenance and reduction of heat radiation

Safe

- Maximum user safety (EMC-tested)
- User-friendly base with non-heated side walls
- No heating without the base, thanks to safety switch
- Stable guide for safe insertion and removal of the bases

Economical

- Long-lasting use thanks to durable materials and electronic components
- Activation of up to 5 bases per minute
- Flexible and efficient use even with fluctuating supply demand
- Use of existing porcelain plates with a diameter of 23 cm

Technical Data and Accessories





Additional system accessories:

- Temp-Trolley for tray transport
- System trolley for bases and domes

Pellet System

Model: Base Advantage Dome Radiance Dome Allure **Diameter:** approx. 24,3 cm approx. 25,6 cm approx. 25,6 cm approx. 69 mm Height: approx. 46 mm approx. 69 mm sapphire blue sapphire blue **Colors:** burgundy burgundy bronze bronze

*With preheated plate and use of a dome from the matching Radiance series

Subject to change, images may show special equipment or differ from the standard. Version: 02/2025

Plate up to \otimes 23 cm

Germany & Luxembourg

Capacity:

temp-rite International GmbH Theodor-Barth-Str. 29 D-28307 Bremen Phone: +49 (0) 4 21-4 86 92-0 E-Mail: info@temp-rite.de

The Netherlands

temp-rite International Holding B.V. Weidehek 64 NL-4842 AS Breda Phone: +31 (0) 76-5 42 43 43 E-Mail: info@temp-rite.nl

an Ali Group Company



Temp-Active Advantage Activator

Model:	TRIHA600
Weight:	15,4 kg
Dimensions: $(W \times D \times H)$	410 x 530 x 290 mm
Wattage and voltage:	5 kW, 400 V
Surface temperature : (min./max.)	105 °C / 115 °C
Activation time:	12 seconds
Holding time:	60 minutes ≥ 60°C*

Belgium

Plate up to \otimes 23 cm

temp-rite International Gemeenteplaats 31 BE-2960 Brecht Phone: +32 (0) 3-3 15 94 65 E-Mail: info@temp-rite.be

Hungary

Plate up to \otimes 23 cm

temp-rite International Kft. Krisztina Krt. 83-85 H-1016 Budapest Phone: +36 (0) 1 212-70 43 E-Mail: sk@temprite.t-online.hu