

We serve the solution

temp-rite

Temp-Trolley



**Lightweight and sturdy ward trolley
for transport of tray systems**

www.temp-rite.eu



CARE

We serve the solution



CLINIC

temp-rite –
Your reliable partner
for innovative and
sustainable solutions in
meal distribution.



temp-rite is double ISO-certified!

Quality management:

Hospitals, old-people's homes and care-providing institutions attach great importance to the quality of the services and products their suppliers deliver. temp-rite's Quality Management System meets all the requirements set out in DIN EN ISO 9001.

Ecological awareness:

temp-rite Germany also has DIN EN ISO 14001 environmental just how seriously we take protecting the environment, and achieving a sustainable balance between commercial and ecological considerations.



Temp-Trolley by temp-rite – Thoughtfully Designed

Temp-Trolley ist ein geschlossener Stationswagen aus einer stabilen Aluminiumprofil-Steckkonstruktion. Die Innenverkleidung besteht aus Edelstahl, mit speziell geformten, tiefgezogenen Sicken, die sich zur Aufnahme diverser Tablett-Versionen eignen.

Die mit FCKW-freiem Schaum isolierten, doppelwandigen Wände und Türen haben einen hohen Isolationswert. Die Türen mit aufwendigem Verschluss sind mit einem Magnethalter ausgestattet, um sie auf 270° offen zu halten. An allen vier Ecken befinden sich senkrechte, ergonomisch geformte

Rundrohr-Schiebegriffe, die für jeden Anwender eine optimale Griffhöhe gewährleisten. Sie sind auf der Abdeckung als Galerie fortgesetzt und durch Eckschutzprofile geschützt. Die obere Abdeckung besteht aus strukturiertem Edelstahl, zum Schutz gegen rasches Verkratzen.

Die unten umlaufende Stoßschutzleiste ist so ausgelegt, dass die Montage eines Kupplungssystems möglich ist. Das Fahrwerk besteht aus zwei Bock- und zwei feststellbaren Lenkrollen mit 160 mm Durchmesser in verzinkt-chromatisierten Gehäusen.

Functional

- Transport of various trays in one trolley
- Passive cooling with eutectic plates (optional)
- Available with cart marking option

Comfortable

- Efficient towing system (optional)
- Easy cleaning of the stainless steel interior
- Gallery for additional supplies

Ergonomical

- Low weight
- Optimal maneuverability
- Ergonomic handles

Flexible

- Various options for individual needs in sizes and capacity
- Needs-based caster configuration

Safe

- Secure fixation of the open doors
- Stable and durable construction
- Optimal transport protection through bumper and corner protection profiles

Economical

- Reduced maintenance and servicing costs
- Quick repair thanks to individually replaceable parts
- Low energy loss due to high-quality insulation

temp-rite delivers optimized meal-distribution systems



Plug-in aluminium profiles

= Stable, lightweight, sturdy



Trolley top with galley rail

= Transport of additional equipment



Towing system (optional)

= Efficient transport of several trolleys with a coupling system



Capacity variety

= Selection of carts with up to 30 GN and EN levels



Various special features

= Flexible options for individual needs



Features, die Ihnen nur der Temp-Trolley bietet

Gewichtsoptimierte Konstruktion

Der Materialmix aus Aluminium- und Edelstahl-Bauteilen bietet höchste Stabilität bei gleichzeitig niedrigem Eigengewicht

= leichteres Handling auch im beladenen Zustand und Vorteile in der Anlieferlogistik durch die Gewichtsersparnis



Geringere Austauschkosten im Schadensfall

Beschädigte Wände, Türen oder Rohre können schnell und leicht ausgetauscht werden

= Wirtschaftlich im Schadensfall, da nur einzelne Komponenten ersetzt werden müssen



Einzigartige Gleitschienen

Spezielle, tiefgezogene Einschübe erlauben die Verwendung verschiedener Tablett in einem Wagen, egal ob Serviertablett, Normtablett oder Isoliertablett

= Variabel nutzbar, praktisch und dabei hygienisch



Passive cooling (option*)

Doors with a condensation collector tray and holders for two GN 1/1-size eutectic plates

= Cold dishes can be served at just the right temperature



*only with a specific door configuration



Double-walled insulation

= Energy-efficient temperature retention of food



Edge profiles and corner bumpers




= Protection of the trolley, contents and surroundings in every transport situation



Ergonomic design

= Comfortable handling thanks to ideal handle height and low weight

Technical Data



Temp-Trolley

Model:	Temp-Trolley 10	Temp-Trolley 20	Temp-Trolley 30
Levels:	1 x 10 GN / EN	2 x 10 GN / EN	3 x 10 GN / EN
Weight:	GN: approx. 60 kg EN: approx. 63 kg	GN: approx. 86 kg EN: approx. 91 kg	GN: approx. 110 kg EN: approx. 116 kg
Dimensions: (W x D x H*)	GN: approx. 570 x 775 x 1.555 mm EN: approx. 615 x 775 x 1.555 mm	GN: approx. 923 x 775 x 1.555 mm EN: approx. 1.013 x 775 x 1.555 mm	GN: approx. 1.276 x 775 x 1.555 mm EN: approx. 1.411 x 775 x 1.555 mm
Tray spacing:	approx. 115 mm	approx. 115 mm	approx. 115 mm

Options and Accessories

- Black Line version
- Passive cooling: doors with condensattion collector tray for holding two GN 1/1 eutectic plates
- Eutectic plates
- Towing system
- Caster with 200 mm diameter
- Caster with stainless steel housing
- Cart marking



*Caster with 160 mm diameter

Subject to change without notice, illustrations may show special equipment or deviate from the standard. As of: 03/2025

Germany & Luxembourg

temp-rite International GmbH
Theodor-Barth-Str. 29
D-28307 Bremen
Phone: +49 (0) 4 21-4 86 92-0
E-Mail: info@temp-rite.de

The Netherlands

temp-rite International Holding B.V.
Weidehek 64
NL-4824 AS Breda
Phone: +31 (0) 76-5 42 43 43
E-Mail: info@temp-rite.nl

Belgium

temp-rite International
Gemeenteplaats 31
BE-2960 Brecht
Phone: +32 (0) 3-3 15 94 65
E-Mail: info@temp-rite.be

Hungary

temp-rite International Kft.
Krisztina Krt. 83 - 85
H-1016 Budapest
Phone: +36 (0) 1 212 70 43
E-Mail: sk@temprite.t-online.hu

an Ali Group Company



the spirit of excellence